

### ROXUL SAFE® 65

### Metal Building Insulation

#### Product Description & Application

ROXUL SAFE® 65 is a mineral wool insulation board approved for use in metal building assemblies where a one hour fire resistance rating is required from one side or both sides of the wall.

	Performance	Test Standard
Compliance	Mineral Fiber Block and Board Thermal Insulation - Type IVB Compliant	ASTM C612
Reaction to Fire	Flame spread index = 0 ; Smoke developed index = 0 Flame spread index = 0 ; Smoke developed index = 0 Determination of Non Combustibility of Building Materials - Non Combustible Test for Non-Combustibility - Non Combustible ULC 1 hr rated from interior side - W605 ULC 1 hr rated from both sides - W610 UL 1 hr rated from interior side - U654 UL 1 hr rated from both sides - U658 Consult UL and ULC Directories for fire rated designs	ASTM E84 (UL 723) CAN/ULC S102 CAN/ULC S114 ASTM E136
Density	Nominal Density, Minimum - 6.0 lbs/ft <sup>3</sup> (96 kgs/m <sup>3</sup> )	ASTM C303
Thermal Resistance	R-Value / inch @ 75°F                      4.2 hr.ft <sup>2</sup> .F/Btu RSI value / 25.4mm @ 24°C                0.74 m <sup>2</sup> K/W	ASTM C518 (C177)
Dimensional Stability	Linear Shrinkage - <1% @ 1200°F	ASTM C356
Corrosion Resistance	Stress Corrosion Cracking Tendency of Austenitic Stainless Steel - Passed Corrosion of Steel - Passed	ASTM C795 ASTM C665
Reaction to Moisture	Moisture Sorption - 0.04% Determination of Fungi Resistance - Passed	ASTM C1104 ASTM C1338
Thickness Dimensions	Product is available in 3" thickness (76.2mm) 24"x48" (610mm x 1219mm), 31.5"x48" (800mm x 1219mm), 32"x48" (813mm x 1219mm)	



Issued 04-01-16  
Supersedes 06-05-12

NOTE: \*Mast Format 1995 Edition \*\*Master Format 2004 Edition. As ROXUL Inc has no control over installation design and workmanship, accessory materials or application conditions, ROXUL Inc. does not warranty the performance or results of any installation containing ROXUL Inc's products. ROXUL Inc's overall liability and the remedies available are limited by the general terms and conditions of sale. This warranty is in lieu of all other warranties and conditions expressed or implied, including the warranties of merchantability and fitness for a particular purpose.